

# DATA SHEET

## Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC Farm Duty - Standard Efficiency Product code : 19181893

Frame	: 182/4T	Locked rotor time	: 12 s (hot) 22 s (cold)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 230 V	Altitude	: 3280 ft
Rated current	: 11.9 A	Protection degree	: IP55
L. R. Amperes	: 118 A	Cooling method	: IC411 - TEFC
LRC	: 9.9	Mounting	: F-2/B3L(E)
No load current	: 7.40 A	Rotation <sup>1</sup>	: Both
Rated speed	: 1770 rpm	Noise level <sup>2</sup>	: 59.0 dB(A)
Slip	: 1.67 %	Vibration class	: A
Rated torque	: 8.75 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 400 %	Approx. weight <sup>3</sup>	: 0.0 lb
Pull up torque	: 340 %	Painting plan	: 207N
Breakdown torque	: 360 %	Color	: RAL 3003
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.3702 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	66.0	74.0	78.5	Load torque	: -
Power Factor	0.75	0.83	0.88	Load inertia (J=GD <sup>2</sup> /4)	: -

Bearing type Lubrication interval Lubricant amount Lubricant type	Drive end	Non drive end	Foundation loads Max. traction : - Max. compression : -
	6206-2RS	6205-2RS	
	-	-	
	-	-	
	MOBIL POLYREX EM		

Notes  
See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.  
(1) Looking the motor from the shaft end.  
(2) Measured at 1m and with tolerance of +3dB(A).  
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1847827739		
Checked by	AUTOMATICO	Page	Rev.	
Date	13/05/2026	1 / 2	0	

# DATA SHEET

## Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC Farm Duty - Standard Efficiency      Product code : 19181893

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.  
(1) Looking the motor from the shaft end.  
(2) Measured at 1m and with tolerance of +3dB(A).  
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1847827739		
Checked by	AUTOMATICO	Page	Rev.	
Date	13/05/2026	2 / 2	0	