

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :				
Product line		: NEMA Premium Efficiency Three-Phase	Product code : 12795531	
Frame		: 213/5T	Cooling method : IC01 - ODP	
Insulation class		: F	Mounting : F-1	
Duty cycle		: Cont.(S1)	Rotation ¹ : Both (CW and CCW)	
Ambient temperature		: -20°C to +40°C	Starting method : Direct On Line	
Altitude		: 1000 m.a.s.l.	Approx. weight ³ : 57.1 kg	
Design		: B	Moment of inertia (J) : 0.0455 kgm ²	
Output [HP]		5		
Poles		6		
Frequency [Hz]		60		
Rated voltage [V]		575		
Rated current [A]		5.39		
L. R. Amperes [A]		31.8		
LRC [A]		5.9x(Code H)		
No load current [A]		2.84		
Rated speed [RPM]		1175		
Slip [%]		2.08		
Rated torque [kgfm]		3.09		
Locked rotor torque [%]		220		
Breakdown torque [%]		250		
Service factor		1.15		
Temperature rise		80 K		
Locked rotor time		52s (cold) 29s (hot)		
Noise level ²		55.0 dB(A)		
Efficiency (%)	25%	88.3		
	50%	88.5		
	75%	89.5		
	100%	89.5		
Power Factor	25%	0.34		
	50%	0.58		
	75%	0.70		
	100%	0.77		
Bearing type		: Drive end 6208 ZZ Non drive end 6206 ZZ	Foundation loads	
Sealing		: Without Without Bearing Seal Bearing Seal	Max. traction : 114 kgf	
Lubrication interval		: - -	Max. compression : 171 kgf	
Lubricant amount		: - -		
Lubricant type		: Mobil Polyrex EM		
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.	
Rev.	Changes Summary		Performed	Checked
Performed by				
Checked by			Page	Revision
Date	17/05/2022		1 / 2	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : NEMA Premium Efficiency Three-Phase Product code : 12795531



Performance : 575 V 60 Hz 6P

Rated current	: 5.39 A	Moment of inertia (J)	: 0.0455 kgm ²
LRC	: 5.9	Duty cycle	: Cont.(S1)
Rated torque	: 3.09 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.15
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 1175 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2 Revision		
Checked by				
Date	17/05/2022			

