# DATA SHEET

## Single Phase Induction Motor - Squirrel Cage

| | |
|---|---|
| Customer | : |

| | | | |
|---|---|---|---|
| Product line | : Jet Pump - J type Single-Phase | Product code : | 14733581 |

| | | | |
|---|---|---|---|
| Frame | : 56J | Cooling method | : IC01 - ODP |
| Insulation class | : F | Mounting | : F-1 |
| Duty cycle | : Cont.(S1) | Rotation[1] | : CCW |
| Ambient temperature | : -20°C to +40°C | Starting method | : Direct On Line |
| Altitude | : 1000 m.a.s.l. | Approx. weight[3] | : 15.6 kg |
| Design | : L | Moment of inertia (J) | : 0.0027 kgm² |

| | | |
|---|---|---|
| Output [HP] | | 1.5 |
| Poles | | 2 |
| Frequency [Hz] | | 60 |
| Rated voltage [V] | | 115/208-230 |
| Rated current [A] | | 12.4/6.86-6.20 |
| L. R. Amperes [A] | | 102/56.3-50.8 |
| LRC [A] | | 8.2x(Code J) |
| No load current [A] | | 3.20/1.38-1.60 |
| Rated speed [RPM] | | 3500 |
| Slip [%] | | 2.78 |
| Rated torque [kgfm] | | 0.311 |
| Locked rotor torque [%] | | 260 |
| Breakdown torque [%] | | 270 |
| Service factor | | |
| Temperature rise | | 80 K |
| Locked rotor time | | 18s (cold) 10s (hot) |
| Noise level[2] | | 58.0 dB(A) |
| Efficiency (%) | 25% | |
| | 50% | 73.0 |
| | 75% | 79.0 |
| | 100% | 81.5 |
| Power Factor | 25% | |
| | 50% | 0.92 |
| | 75% | 0.95 |
| | 100% | 0.95 |

| | | Drive end | Non drive end |
|---|---|---|---|
| Bearing type | : | 6203 2RS | 6202 2RS |
| Sealing | : | Without Bearing Seal | Without Bearing Seal |
| Lubrication interval | : | - | - |
| Lubricant amount | : | - | - |
| Lubricant type | : | Mobil Polyrex EM | |

Foundation loads

Max. traction : 19 kgf

Max. compression : 34 kgf

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |


| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 17/05/2022 | | 1 / 2 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

# LOAD PERFORMANCE CURVE

## Single Phase Induction Motor - Squirrel Cage

| | | | |
|---|---|---|---|
| Customer | : | | |
| Product line | : Jet Pump - J type Single-Phase | Product code : | 14733581 |






| | | | |
|---|---|---|---|
| Performance | : 115/208-230 V 60 Hz 2P | | |
| Rated current | : 12.4/6.86-6.20 A | Moment of inertia (J) | : 0.0027 kgm² |
| LRC | : 8.2 | Duty cycle | : Cont.(S1) |
| Rated torque | : 0.311 kgfm | Insulation class | : F |
| Locked rotor torque | : 260 % | Service factor | : |
| Breakdown torque | : 270 % | Temperature rise | : 80 K |
| Rated speed | : 3500 rpm | Design | : L |


| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 17/05/2022 | | 2 / 2 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice




Color Munsell N 1 matte black

Painting plan 207N

Mounting F-1/B14R(D)

| ECM | LOC | SUMMARY OF MODIFICATIONS | EXECUTED | CHECKED | RELEASED | DATE | VER |
|---|---|---|---|---|---|---|---|
| | | | HYBRISUSER | | | | 00 |

| | | | | | |
|---|---|---|---|---|---|
| EXECUTED | HYBRISUSER | SINGLE PH. MOTOR ROLLED STEEL JET PUMP THREADED PREM.EFF. | PREVIEW | | |
| CHECKED | | FRAME 56J IP21 ODP | | | |
| RELEASED | | | WDD | 00 | |
| REL. DATE | | WMO Jaragua do Sul Product Engineering | SHEET | 1 / 1 | |

1.5 HP 02 Poles 60 Hz

A

Dimensions in inches

XME A3

WEG's property. Forbidden reproduction without previous authorization.