

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Premium Efficiency (DOE)

Frame	: W56	Locked rotor time	: 21 s (hot) 38 s (cold)
Output	: 0.25 HP (0.18 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 115/208-230 V	Altitude	: 3280 ft
Rated current	: 2.52/1.40-1.26 A	Protection degree	: IP55
L. R. Amperes	: 22.7/12.6-11.3 A	Cooling method	: IC411 - TEFC
LRC	: 9.0	Mounting	: F-1/B3R(D)
No load current	: 1.00/0.431-0.500 A	Rotation ¹	: Both
Rated speed	: 3510 rpm	Noise level ²	: 66.0 dB(A)
Slip	: 2.50 %	Vibration class	: A
Rated torque	: 0.369 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 290 %	Approx. weight ³	: 22.3 lb
Pull up torque	: 245 %	Color	: PRIMER ONLY
Breakdown torque	: 300 %	Design	: N
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0261 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	50.0	59.5	68.0	Load torque	: -
Power Factor	0.87	0.89	0.91	Load inertia (J=GD ² /4)	: -
	Drive end	Non drive end		Foundation loads	
Bearing type #1	6203-ZZ	6202-ZZ		Max. traction	: -
Bearing type #2	-	-		Max. compression	: -
Lubrication interval	-	-			
Lubricant amount #1	-	-			
Lubricant amount #2	-	-			
Lubricant type	MOBIL POLYREX EM				

Notes

See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1861514080	
Checked by	AUTOMATICO			Page	Rev.
Date	16/06/2026			1 / 2	0

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Premium Efficiency (DOE)

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7		
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12		
	Noise	: MG1 - Part 9				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight, subject to be changed after manufacturing process.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.			
Rev.		Changes Summary		Rev.	Checked	Date
Performed by		farazq	1861514080			
Checked by		AUTOMATICO				
Date		16/06/2026				
			Page	Rev.		
			2 / 2	0		

