

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : General High Efficiency Three-Phase Product code : 11074488

Frame	: 182TC	Cooling method	: IC01 - ODP
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 27.8 kg
Protection degree	: IP21	Moment of inertia (J)	: 0.0054 kgm ²
Design	: B		

Output [HP]	5	5	5	5
Poles	2	2	2	2
Frequency [Hz]	60	50	50	50
Rated voltage [V]	230/460	380	400	415
Rated current [A]	12.5/6.24	7.74	7.39	7.30
L. R. Amperes [A]	88.6/44.3	43.3	45.8	48.2
LRC [A]	7.1x(Code H)	5.6x(Code G)	6.2x(Code H)	6.6x(Code H)
No load current [A]	5.60/2.80	2.70	3.30	3.80
Rated speed [RPM]	3510	2875	2890	2900
Slip [%]	2.50	4.17	3.67	3.33
Rated torque [kgfm]	1.03	1.26	1.26	1.25
Locked rotor torque [%]	180	150	160	180
Breakdown torque [%]	290	210	240	260
Service factor	1.15	1.00	1.00	1.00
Temperature rise	105 K	105 K	105 K	105 K
Locked rotor time	21s (cold) 12s (hot)	28s (cold) 16s (hot)	25s (cold) 14s (hot)	21s (cold) 12s (hot)
Noise level ²	64.0 dB(A)			
Efficiency (%)	25%			
	50%	85.5	82.5	82.5
	75%	86.5	84.0	84.0
	100%	86.5	82.5	84.0
Power Factor	25%			
	50%	0.70	0.76	0.71
	75%	0.80	0.85	0.82
	100%	0.86	0.88	0.86

Bearing type	: <u>Drive end</u> 6206 ZZ	<u>Non drive end</u> 6205 ZZ	Foundation loads	Max. traction : 54 kgf
	: Without	Without		
Sealing	Bearing Seal Bearing Seal			
Lubrication interval	-			
Lubricant amount	-			
Lubricant type	Mobil Polyrex EM			

Notes
USABLE @208V 13.6A SF 1.15 SFA 15.7A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : General High Efficiency Three-Phase

Product code : 11074488



Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 2 / 5
Checked by				
Date				
		Revision		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : General High Efficiency Three-Phase

Product code : 11074488



Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 5		Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : General High Efficiency Three-Phase

Product code : 11074488



Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 4 / 5		Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General High Efficiency Three-Phase

Product code : 11074488



Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 5		Revision
Checked by				
Date				

