

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 13500700

Frame	: 586/7TZ	Locked rotor time	: 45s (cold) 25s (hot)
Output	: 400 HP (300 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 460 V	Ambient temperature	: -20°C to +40°C
Poles	: 4	Altitude	: 1000 m.a.s.l.
Rated current	: 466 A	Protection degree	: IP55
	: 7.1x(Code H)	Cooling method	: IC411 - TEFC
Rated speed	: 1791 rpm	Mounting	: F-1
Rated torque	: 162 kgfm	Rotation ¹	: Both (CW and CCW)
Insulation class	: F	Noise level ²	: 78.0 dB(A)
Service factor	: 1.15	Starting method	: Direct On Line
Moment of inertia (J)	: 7.52 kgm ²	Approx. weight ³	: 1567 kg
Design	: A		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	0.000	95.8	96.2	96.2	Max. traction : 1879 kgf
Power Factor	0.00	0.73	0.81	0.84	Max. compression : 3446 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	NU-324 C3	6319 C3
Sealing	:	Taconite Labyrinth	Taconite Labyrinth
Lubrication interval	:	3000 h	8000 h
Lubricant amount	:	72 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes

W22 Crusher Duty - NEMA Premium Efficiency

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 3		
Checked by				
Date	28/05/2026			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 3	
Date	28/05/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 13500700



Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3Revision		
Checked by				
Date	28/05/2026			

