DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W40 High Efficiency Three-Phase Product code : 14282771

Frame	: 404/5TS	Locked rotor time	: 21s (cold) 12s (hot)
Output	: 125 HP	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 110 A	Protection degree	: IP23
L. R. Amperes	: 724 A	Cooling method	: IC01 - ODP
LRC	: 6.6x(Code G)	Mounting	: F-1
No load current	: 26.4 A	Rotation[1]	: Both (CW and CCW)
Rated speed	: 3545 rpm	Noise level[2]	: 84.0 dB(A)
Slip	: 1.53 %	Starting method	: Direct On Line
Rated torque	: 25.6 kgfm	Approx. weight[3]	: 398 kg
Locked rotor torque	: 180 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.3384 kgm²		
Design	: B		

Output	50%	75%	100%
Efficiency (%)	93.0	93.6	93.6
Power Factor	0.80	0.86	0.88

Foundation loads

Max. traction	: 387 kgf
Max. compression	: 770 kgf

		Drive end	Non drive end
Bearing type	:	6314 C3	6212 Z C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	14418 h	20000 h
Lubricant amount	:	27 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	14/07/2026		1 / 2	


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W40 High Efficiency Three-Phase Product code : 14282771





Performance	: 575 V 60 Hz 2P		
Rated current	: 110 A	Moment of inertia (J)	: 0.3384 kgm²
LRC	: 6.6	Duty cycle	: Cont.(S1)
Rated torque	: 25.6 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.15
Breakdown torque	: 229 %	Temperature rise	: 80 K
Rated speed	: 3545 rpm	Design	: B


Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	14/07/2026		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice








Color RAL 3002

Painting plan 203A

Mounting NEMA F-1

Mounting B3R(D)

DE Shaft End



DUNC 3/4"-10 WEG WPR-7339

125 HP 02 Poles 60 Hz

A

Scale 1 : 12

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
		DATAVIEWERUSER					00

EXECUTED DATAVIEWERUSER

CHECKED

RELEASED

REL. DATE

THREE PH. MOTOR W40 HIGH EFF.

FRAME 404/5TS IP23 ODP

PREVIEW

WDD 00

SHEET 1 / 1

Dimensions in inches

A3

WEG's property. Forbidden reproduction without previous authorization.