

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Premium Efficiency (DOE)

Frame	: W56	Locked rotor time	: 30 s (hot) 54 s (cold)
Output	: 0.25 HP (0.18 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 208-230/460 V	Altitude	: 3280 ft
Rated current	: 1.01-0.912/0.456 A	Protection degree	: IP55
L. R. Amperes	: 7.47-6.75/3.37 A	Cooling method	: IC411 - TEFC
LRC	: 7.4	Mounting	: F-1/B3R(D)
No load current	: 0.497-0.576/0.288 A	Rotation ¹	: Both
Rated speed	: 3460 rpm	Noise level ²	: 65.0 dB(A)
Slip	: 3.89 %	Vibration class	: A
Rated torque	: 0.376 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 350 %	Approx. weight ³	: 16.2 lb
Pull up torque	: 295 %	Color	: PRIMER ONLY
Breakdown torque	: 400 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0142 sq.ft.lb		

Output	50%	75%	100%
Efficiency (%)	55.0	62.0	66.0
Power Factor	0.60	0.70	0.75

Load type	: -
Load torque	: -
Load inertia (J=GD ² /4)	: -

	Drive end	Non drive end
Bearing type	6203-ZZ	6202-ZZ
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	MOBIL POLYREX EM	

Foundation loads	
Max. traction	: 29 N
Max. compression	: 102 N

Notes

See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq		1856291396		
Checked by	AUTOMATICO		Page	Rev.	
Date	03/06/2026		1 / 2	0	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Premium Efficiency (DOE)

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight, subject to be changed after manufacturing process.	These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.
---	---

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1856291396		
Checked by	AUTOMATICO	Page	Rev.	
Date	03/06/2026	2 / 2	0	

