

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 High Efficiency Three-Phase Product code : 14282975

Frame	: 444/5TS	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 250 HP (185 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 229 A	Protection degree	: IP23
L. R. Amperes	: 1463 A	Cooling method	: IC01 - ODP
LRC	: 6.4x(Code G)	Mounting	: F-1
No load current	: 65.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3560 rpm	Starting method	: Direct On Line
Slip	: 1.11 %	Approx. weight ³	: 637 kg
Rated torque	: 51.0 kgfm		
Locked rotor torque	: 130 %		
Breakdown torque	: 220 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 1.00 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	93.6	94.5	94.5	Max. traction	: 681 kgf
Power Factor	0.77	0.84	0.86	Max. compression	: 1280 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6212 Z C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	14418 h	20000 h
Lubricant amount	:	27 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	14/07/2026			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :



Product line : W40 High Efficiency Three-Phase Product code : 14282975



Performance : 575 V 60 Hz 2P

Rated current	: 229 A	Moment of inertia (J)	: 1.00 kgm ²
LRC	: 6.4	Duty cycle	: Cont.(S1)
Rated torque	: 51.0 kgfm	Insulation class	: F
Locked rotor torque	: 130 %	Service factor	: 1.15
Breakdown torque	: 220 %	Temperature rise	: 80 K
Rated speed	: 3560 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2 Revision		
Checked by				
Date	14/07/2026			



250 HP 02 Poles 60 Hz										A
						Scale				1 : 14
						HYBRISUSER				00
ECM		LOC		SUMMARY OF MODIFICATIONS		EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER		THREE PH. MOTOR W40 HIGH EFF. FRAME 444/5TS IP23 ODP			PREVIEW				
CHECKED						WDD	00			
RELEASED										
REL. DATE										
						SHEET		1 / 1		