

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :				
Product line : Single-Phase		Product code : 13490020		
Frame : 56HC Insulation class : F Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Design : L		Cooling method : IC411 - TEFC Mounting : F-1 Rotation ¹ : Both (CW and CCW) Starting method : Direct On Line Approx. weight ³ : 20.8 kg Moment of inertia (J) : 0.0082 kgm²		
Output [HP]	1			
Poles	6			
Frequency [Hz]	60			
Rated voltage [V]	115/208-230			
Rated current [A]	11.0/6.08-5.50			
L. R. Amperes [A]	67.1/37.1-33.5			
LRC [A]	6.1x(Code J)			
No load current [A]	5.60/2.41-2.80			
Rated speed [RPM]	1165			
Slip [%]	2.92			
Rated torque [kgfm]	0.623			
Locked rotor torque [%]	180			
Breakdown torque [%]	200			
Service factor				
Temperature rise	80 K			
Locked rotor time	23s (cold) 13s (hot)			
Noise level ²	54.0 dB(A)			
Efficiency (%)	25%			
	50%	64.0		
	75%	71.0		
	100%	73.0		
Power Factor	25%			
	50%	0.68		
	75%	0.77		
	100%	0.81		
Bearing type : Drive end 6204 ZZ Non drive end 6202 ZZ Sealing : V'Ring Without Bearing Seal Lubrication interval : - - Lubricant amount : - - Lubricant type : Mobil Polyrex EM		Foundation loads Max. traction : 29 kgf Max. compression : 50 kgf		
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked
Performed by				
Checked by			Page	Revision
Date	13/05/2022		1 / 2	

LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Single-Phase

Product code : 13490020





Performance : 115/208-230 V 60 Hz 6P

Rated current : 11.0/6.08-5.50 A
 LRC : 6.1
 Rated torque : 0.623 kgfm
 Locked rotor torque : 180 %
 Breakdown torque : 200 %
 Rated speed : 1165 rpm

Moment of inertia (J) : 0.0082 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 80 K
 Design : L

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2Revision		
Checked by				
Date	13/05/2022			



Color Munsell N 1 matte black									
Painting plan 207N									
Mounting B34D									
						HYBRISUSER			00
ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE VER
EXECUTED	HYBRISUSER					PREVIEW			
CHECKED									
RELEASED									
REL. DATE		WMO	Jaragua do Sul	Product Engineering	SHEET	1	/	1	