DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Standard Efficiency Three-Phase	Product code :	12894764

Frame	: 56HC	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation[1]	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight[3]	: 17.0 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0052 kgm²
Design	: A		

Output [HP]		2	1.5	1.5
Poles		4	4	4
Frequency [Hz]		60	50	50
Rated voltage [V]		230/460	190/380	220/415
Rated current [A]		5.70/2.85	5.24/2.62	4.96/2.63
L. R. Amperes [A]		41.6/20.8	38.3/19.1	38.2/20.3
LRC [A]		7.3x(Code K)	7.3x(Code K)	7.7x(Code L)
No load current [A]		3.33/1.66	3.23/1.61	3.52/1.87
Rated speed [RPM]		1745	1445	1450
Slip [%]		3.06	3.67	3.33
Rated torque [kgfm]		0.832	0.753	0.751
Locked rotor torque [%]		240	250	280
Breakdown torque [%]		270	290	320
Service factor			1.15	1.15
Temperature rise		80 K	80 K	80 K
Locked rotor time		14s (cold) 8s (hot)	0s (cold) 0s (hot)	0s (cold) 0s (hot)
Noise level[2]		52.0 dB(A)	49.0 dB(A)	49.0 dB(A)
Efficiency (%)	25%	78.9	77.4	74.4
	50%	80.0	77.8	75.6
	75%	81.5	80.6	79.6
	100%	82.5	80.6	80.5
Power Factor	25%	0.33	0.32	0.29
	50%	0.58	0.57	0.52
	75%	0.72	0.71	0.66
	100%	0.80	0.79	0.75

		Drive end	Non drive end
Bearing type	:	6204 ZZ	6202 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Foundation loads

Max. traction : 69 kgf

Max. compression : 86 kgf

Notes

USABLE @208V 6.30A SF 1.00 SFA 6.30A

This revision replaces and cancel the previous one, which must be eliminated.

(1) Looking the motor from the shaft end.

(2) Measured at 1m and with tolerance of +3dB(A).

(3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	13/05/2022		1 / 4	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: Standard Efficiency Three-Phase	Product code :	12894764



Performance	: 230/460 V 60 Hz 4P		
Rated current	: 5.70/2.85 A	Moment of inertia (J)	: 0.0052 kgm²
LRC	: 7.3	Duty cycle	: Cont.(S1)
Rated torque	: 0.832 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	:
Breakdown torque	: 270 %	Temperature rise	: 80 K
Rated speed	: 1745 rpm	Design	: A

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	13/05/2022		2 / 4	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: Standard Efficiency Three-Phase	Product code :	12894764



Performance	: 190/380 V 50 Hz 4P		
Rated current	: 5.24/2.62 A	Moment of inertia (J)	: 0.0052 kgm²
LRC	: 7.3	Duty cycle	: Cont.(S1)
Rated torque	: 0.753 kgfm	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.15
Breakdown torque	: 290 %	Temperature rise	: 80 K
Rated speed	: 1445 rpm	Design	: A

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	13/05/2022		3 / 4	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: Standard Efficiency Three-Phase	Product code :	12894764




Performance	: 220/415 V 50 Hz 4P		
Rated current	: 4.96/2.63 A	Moment of inertia (J)	: 0.0052 kgm²
LRC	: 7.7	Duty cycle	: Cont.(S1)
Rated torque	: 0.751 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.15
Breakdown torque	: 320 %	Temperature rise	: 80 K
Rated speed	: 1450 rpm	Design	: A

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	13/05/2022		4 / 4	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice



			HYBRISUSER				00
ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER

Color Munsell N 1 matte black

Painting plan 207N

Mounting B34D

EXECUTED	HYBRISUSER
CHECKED	
RELEASED	
REL. DATE	

THREE PH. MOTOR ROLLED STEEL

FRAME 56HC IP55 TEFC

WMO Jaragua do Sul Product Engineering

PREVIEW

WDD 00

SHEET 1 / 1

2 HP 04 Poles 60 Hz

A

Dimensions in inches

XME A3

WEG's property. Forbidden reproduction without previous authorization.