DATA SHEET

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line	: Farm Duty Single-Phase	Product code :	10371504

Frame	: B56	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 0.5 HP (0.37 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.44/3.72 A	Protection degree	: IP55
L. R. Amperes	: 43.2/21.6 A	Cooling method	: IC411 - TEFC
LRC	: 5.8x(Code L)	Mounting	: F-1
No load current	: 6.00/3.00 A	Rotation[1]	: Both (CW and CCW)
Rated speed	: 1750 rpm	Noise level[2]	: 55.0 dB(A)
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 0.207 kgfm	Approx. weight[3]	: 11.2 kg
Locked rotor torque	: 290 %		
Breakdown torque	: 270 %		
Insulation class	: B		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0034 kgm²		

Output	25%	50%	75%	100%
Efficiency (%)	53.8	56.0	64.0	66.5
Power Factor	0.25	0.46	0.57	0.65

Foundation loads

Max. traction	: 12 kgf
Max. compression	: 23 kgf

		Drive end	Non drive end
Bearing type	:	6203 ZZ	6202 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	20/10/2024		1 / 2	


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : Farm Duty Single-Phase Product code : 10371504





Performance	: 115/230 V 60 Hz 4P		
Rated current	: 7.44/3.72 A	Moment of inertia (J)	: 0.0034 kgm²
LRC	: 5.8	Duty cycle	: Cont.(S1)
Rated torque	: 0.207 kgfm	Insulation class	: B
Locked rotor torque	: 290 %	Service factor	: 1.15
Breakdown torque	: 270 %	Temperature rise	: 80 K
Rated speed	: 1750 rpm		


Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	20/10/2024		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice







Rotation CW and CCW

Mounting B3R(D)

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER	SINGLE PH. MOTOR FARM DUTY	PREVIEW		
CHECKED		FRAME B56 IP55 TEFC	WDD	00	
RELEASED					
REL. DATE		WMO Jaragua do Sul Product Engineering	SHEET	1 / 1	

1/2 HP 04 Poles 60 Hz

A

Dimensions in inches

XME A3

WEG's property. Forbidden reproduction without previous authorization.