

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :				
Product line		: NEMA Premium Efficiency Three-Phase	Product code : 12675407	
Frame		: 213/5T	Cooling method : IC411 - TEFC	
Insulation class		: F	Mounting : F-1	
Duty cycle		: Cont.(S1)	Rotation ¹ : Both (CW and CCW)	
Ambient temperature		: -20°C to +40°C	Starting method : Direct On Line	
Altitude		: 1000 m.a.s.l.	Approx. weight ³ : 57.9 kg	
Protection degree		: IP55	Moment of inertia (J) : 0.0451 kgm ²	
Design		: B		
Output [HP]		10		
Poles		4		
Frequency [Hz]		60		
Rated voltage [V]		575		
Rated current [A]		9.76		
L. R. Amperes [A]		68.3		
LRC [A]		7.0x(Code H)		
No load current [A]		4.43		
Rated speed [RPM]		1760		
Slip [%]		2.22		
Rated torque [kgfm]		4.12		
Locked rotor torque [%]		250		
Breakdown torque [%]		300		
Service factor		1.15		
Temperature rise		80 K		
Locked rotor time		27s (cold) 15s (hot)		
Noise level ²		60.0 dB(A)		
Efficiency (%)	25%	90.2		
	50%	91.0		
	75%	91.0		
	100%	91.7		
Power Factor	25%	0.41		
	50%	0.67		
	75%	0.78		
	100%	0.84		
Bearing type		Drive end : 6208 ZZ	Non drive end : 6206 ZZ	Foundation loads
Sealing		V'Ring	Without Bearing Seal	Max. traction : 200 kgf
Lubrication interval		-	-	Max. compression : 258 kgf
Lubricant amount		-	-	
Lubricant type		Mobil Polyrex EM		
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.	
Rev.	Changes Summary		Performed	Checked
Performed by				
Checked by			Page	Revision
Date	13/05/2022		1 / 2	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : NEMA Premium Efficiency Three-Phase Product code : 12675407



Performance : 575 V 60 Hz 4P

Rated current	: 9.76 A	Moment of inertia (J)	: 0.0451 kgm ²
LRC	: 7.0	Duty cycle	: Cont.(S1)
Rated torque	: 4.12 kgfm	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.15
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 1760 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2 Revision		
Checked by				
Date	13/05/2022			

