

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11939518

Frame	: 182/4TC	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 51.5 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0094 kgm ²
Design	: B		

Output [HP]	5	4	4	4	5	5	5
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	5.90	5.79	5.57	5.43	7.14	6.78	6.61
L. R. Amperes [A]	44.8	42.8	45.1	48.3	42.1	44.7	47.6
LRC [A]	7.6x(Code J)	7.4x(Code H)	8.1x(Code J)	8.9x(Code K)	5.9x(Code F)	6.6x(Code G)	7.2x(Code H)
No load current [A]	2.00	2.00	2.15	2.25	2.00	2.15	2.25
Rated speed [RPM]	3485	2890	2900	2910	2850	2870	2880
Slip [%]	3.19	3.67	3.33	3.00	5.00	4.33	4.00
Rated torque [kgfm]	1.04	1.00	1.00	0.998	1.27	1.26	1.26
Locked rotor torque [%]	229	229	270	300	180	210	240
Breakdown torque [%]	350	320	370	400	250	290	320
Service factor	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	45s (cold) 25s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)
Noise level ²	66.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)
Efficiency (%)	25%						
	50%	86.5	86.3	86.3	86.1	87.5	87.5
	75%	88.5	87.7	88.2	88.2	87.5	88.5
	100%	88.5	87.5	88.3	88.3	86.5	87.5
Power Factor	25%						
	50%	0.76	0.74	0.71	0.68	0.81	0.76
	75%	0.85	0.85	0.83	0.81	0.88	0.87
	100%	0.89	0.90	0.88	0.87	0.91	0.90

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	12.4	12.4	12.4	12.4	12.4	12.4	12.4
	P2 (0,5;1,0)	9.9	9.9	9.9	9.9	9.9	9.9	9.9
	P3 (0,25;1,0)	8.9	8.9	8.9	8.9	8.9	8.9	8.9
	P4 (0,9;0,5)	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	P5 (0,5;0,5)	3.7	3.7	3.7	3.7	3.7	3.7	3.7
	P6 (0,5;0,25)	2.3	2.3	2.3	2.3	2.3	2.3	2.3
	P7 (0,25;0,25)	1.4	1.4	1.4	1.4	1.4	1.4	1.4

Bearing type	: 6207 C3	Non drive end	6206 C3	Foundation loads	
Sealing	: Taconite		Taconite	Max. traction	: 58 kgf
	: Labyrinth		Labyrinth	Max. compression	: 110 kgf
Lubrication interval	: 20000 h		20000 h		
Lubricant amount	: 7 g		5 g		
Lubricant type	: Mobil Polyrex EM				

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	22/10/2024		1 / 9	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11939518



Performance : 460 V 60 Hz 2P

Rated current : 5.90 A
LRC : 7.6
Rated torque : 1.04 kgfm
Locked rotor torque : 229 %
Breakdown torque : 350 %
Rated speed : 3485 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 9	Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11939518



Performance : 380 V 50 Hz 2P IE3

Rated current : 5.79 A
LRC : 7.4
Rated torque : 1.00 kgfm
Locked rotor torque : 229 %
Breakdown torque : 320 %
Rated speed : 2890 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11939518



Performance : 400 V 50 Hz 2P IE3

Rated current : 5.57 A
LRC : 8.1
Rated torque : 1.00 kgfm
Locked rotor torque : 270 %
Breakdown torque : 370 %
Rated speed : 2900 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11939518

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 2P IE3

Rated current	: 5.43 A	Moment of inertia (J)	: 0.0094 kgm ²
LRC	: 8.9	Duty cycle	: Cont.(S1)
Rated torque	: 0.998 kgfm	Insulation class	: F
Locked rotor torque	: 300 %	Service factor	: 1.25
Breakdown torque	: 400 %	Temperature rise	: 80 K
Rated speed	: 2910 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 6 / 9 Revision			
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11939518



Performance : 380 V 50 Hz 2P IE2

Rated current : 7.14 A
LRC : 5.9
Rated torque : 1.27 kgfm
Locked rotor torque : 180 %
Breakdown torque : 250 %
Rated speed : 2850 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 7 / 9	Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11939518

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 2P IE2			
Rated current	: 6.78 A	Moment of inertia (J)	: 0.0094 kgm²
LRC	: 6.6	Duty cycle	: Cont.(S1)
Rated torque	: 1.26 kgfm	Insulation class	: F
Locked rotor torque	: 210 %	Service factor	: 1.25
Breakdown torque	: 290 %	Temperature rise	: 80 K
Rated speed	: 2870 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11939518



Performance : 415 V 50 Hz 2P IE2

Rated current : 6.61 A
LRC : 7.2
Rated torque : 1.26 kgfm
Locked rotor torque : 240 %
Breakdown torque : 320 %
Rated speed : 2880 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 9 / 9	Revision
Checked by					
Date	22/10/2024				

