

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium Efficiency Three-Phase

Product code : 12676960

Frame	: 143/5JM	Cooling method	: IC01 - ODP
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 19.9 kg
Design	: B	Moment of inertia (J)	: 0.0060 kgm ²

Output [HP]	1.5	1.5	1.5
Poles	4	4	4
Frequency [Hz]	60	50	50
Rated voltage [V]	230/460	190/380	220/415
Rated current [A]	4.14/2.07	4.84/2.42	4.41/2.34
L. R. Amperes [A]	36.0/18.0	31.0/15.5	30.9/16.4
LRC [A]	8.7x(Code L)	6.4x(Code H)	7.0x(Code J)
No load current [A]	2.40/1.20	2.36/1.18	2.41/1.28
Rated speed [RPM]	1760	1440	1445
Slip [%]	2.22	4.00	3.67
Rated torque [kgfm]	0.619	0.756	0.753
Locked rotor torque [%]	280	190	220
Breakdown torque [%]	330	250	280
Service factor		1.15	1.15
Temperature rise	80 K	80 K	80 K
Locked rotor time	27s (cold) 15s (hot)	0s (cold) 0s (hot)	0s (cold) 0s (hot)
Noise level ²	52.0 dB(A)	49.0 dB(A)	49.0 dB(A)
Efficiency (%)	25%	83.6	85.3
	50%	84.0	84.3
	75%	86.5	84.7
	100%	86.5	83.2
Power Factor	25%	0.32	0.38
	50%	0.56	0.64
	75%	0.69	0.77
	100%	0.77	0.83

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type	: 6206 ZZ	6203 ZZ	Max. traction : 50 kgf
Sealing	: Without	Without	Max. compression : 70 kgf
	Bearing Seal	Bearing Seal	
Lubrication interval	: -	-	
Lubricant amount	: -	-	
Lubricant type	: Mobil Polyrex EM		

Notes

USABLE @208V 4.58A SF 1.00 SFA 4.58A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	16/05/2022			

Page 1 / 4
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12676960



Performance : 230/460 V 60 Hz 4P

Rated current : 4.14/2.07 A
 LRC : 8.7
 Rated torque : 0.619 kgfm
 Locked rotor torque : 280 %
 Breakdown torque : 330 %
 Rated speed : 1760 rpm

Moment of inertia (J) : 0.0060 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 4	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12676960



Performance : 190/380 V 50 Hz 4P

Rated current : 4.84/2.42 A
LRC : 6.4
Rated torque : 0.756 kgfm
Locked rotor torque : 190 %
Breakdown torque : 250 %
Rated speed : 1440 rpm

Moment of inertia (J) : 0.0060 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 4Revision		
Checked by				
Date	16/05/2022			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12676960







Performance : 220/415 V 50 Hz 4P


Rated current : 4.41/2.34 A
LRC : 7.0
Rated torque : 0.753 kgfm
Locked rotor torque : 220 %
Breakdown torque : 280 %
Rated speed : 1445 rpm

Moment of inertia (J) : 0.0060 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 4	Revision
Checked by					
Date	16/05/2022				



EUNC 3/8"-16 WEG WPR-7309-

Color Munsell N 1 matte black									
Painting plan 207N									
Mounting B34D									
						HYBRISUSER			00
ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE VER
EXECUTED	HYBRISUSER		THREE PH. MOTOR ROLLED STEEL JM NEMA PREM. EFF.			PREVIEW WDD 00			
CHECKED			FRAME 143/5JM IP21 ODP						
RELEASED									
REL. DATE		WMO	Jaragua do Sul	Product Engineering	SHEET	1 / 1			

WEG's property. Forbidden reproduction without previous authorization.

Dimensions in inches

KME	A3
-----	----