

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12676946

Frame	: 143/5JM	Cooling method	: IC01 - ODP
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 19.0 kg
Design	: B	Moment of inertia (J)	: 0.0054 kgm ²

Output [HP]	3	3	3
Poles	2	2	2
Frequency [Hz]	60	50	50
Rated voltage [V]	230/460	190/380	220/415
Rated current [A]	7.18/3.59	8.78/4.39	7.83/4.15
L. R. Amperes [A]	57.4/28.7	53.6/26.8	53.2/28.2
LRC [A]	8.0x(Code J)	6.1x(Code G)	6.8x(Code H)
No load current [A]	2.60/1.30	2.60/1.30	2.71/1.44
Rated speed [RPM]	3480	2825	2840
Slip [%]	3.33	5.83	5.33
Rated torque [kgfm]	0.626	0.771	0.767
Locked rotor torque [%]	229	190	220
Breakdown torque [%]	300	229	250
Service factor		1.00	1.00
Temperature rise	80 K	105 K	105 K
Locked rotor time	16s (cold) 9s (hot)	0s (cold) 0s (hot)	0s (cold) 0s (hot)
Noise level ²	62.0 dB(A)	60.0 dB(A)	60.0 dB(A)
Efficiency (%)	25%	83.7	89.4
	50%	84.0	86.6
	75%	85.5	85.0
	100%	85.5	81.8
Power Factor	25%	0.50	0.56
	50%	0.76	0.83
	75%	0.86	0.90
	100%	0.90	0.93

	<u>Drive end</u>	<u>Non drive end</u>	
Bearing type	: 6206 ZZ	6203 ZZ	Foundation loads
Sealing	: Without	Without	Max. traction : 45 kgf
	Bearing Seal	Bearing Seal	Max. compression : 64 kgf
Lubrication interval	: -	-	
Lubricant amount	: -	-	
Lubricant type	: Mobil Polyrex EM		

Notes

USABLE @208V 7.94A SF 1.00 SFA 7.94A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	16/05/2022			

Page 1 / 4
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12676946



Performance : 230/460 V 60 Hz 2P

Rated current : 7.18/3.59 A
LRC : 8.0
Rated torque : 0.626 kgfm
Locked rotor torque : 229 %
Breakdown torque : 300 %
Rated speed : 3480 rpm

Moment of inertia (J) : 0.0054 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor :
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 4	Revision
Checked by					
Date	16/05/2022				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12676946



Performance : 190/380 V 50 Hz 2P

Rated current : 8.78/4.39 A
LRC : 6.1
Rated torque : 0.771 kgfm
Locked rotor torque : 190 %
Breakdown torque : 229 %
Rated speed : 2825 rpm

Moment of inertia (J) : 0.0054 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 3 / 4
Checked by				
Date				
16/05/2022				Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12676946



Performance : 220/415 V 50 Hz 2P

Rated current : 7.83/4.15 A
LRC : 6.8
Rated torque : 0.767 kgfm
Locked rotor torque : 220 %
Breakdown torque : 250 %
Rated speed : 2840 rpm

Moment of inertia (J) : 0.0054 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date	
Performed by					Page 4 / 4	Revision
Checked by						
Date	16/05/2022					

