

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium Efficiency Three-Phase

Product code : 13180570

Frame	: 213/5JM	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 64.0 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0451 kgm ²
Design	: B		

Output [HP]	10	7.5	7.5
Poles	4	4	4
Frequency [Hz]	60	50	50
Rated voltage [V]	230/460	190/380	220/415
Rated current [A]	24.4/12.2	22.4/11.2	20.8/11.0
L. R. Amperes [A]	171/85.4	170/85.1	172/91.3
LRC [A]	7.0x(Code H)	7.6x(Code J)	8.3x(Code K)
No load current [A]	11.1/5.54	10.9/5.46	11.3/5.97
Rated speed [RPM]	1760	1465	1470
Slip [%]	2.22	2.33	2.00
Rated torque [kgfm]	4.12	3.72	3.70
Locked rotor torque [%]	250	250	290
Breakdown torque [%]	300	320	360
Service factor	1.15	1.15	1.15
Temperature rise	80 K	80 K	80 K
Locked rotor time	27s (cold) 15s (hot)	0s (cold) 0s (hot)	0s (cold) 0s (hot)
Noise level ²	60.0 dB(A)	57.0 dB(A)	57.0 dB(A)
Efficiency (%)	25%	90.2	89.3
	50%	91.0	89.4
	75%	91.0	90.5
	100%	91.7	90.3
Power Factor	25%	0.41	0.34
	50%	0.67	0.59
	75%	0.78	0.73
	100%	0.84	0.80

Bearing type	Drive end	Non drive end	Foundation loads
	6209 ZZ	6206 ZZ	
Sealing	V'Ring	Without Bearing Seal	Max. traction : 214 kgf Max. compression : 278 kgf
Lubrication interval	:	-	
Lubricant amount	:	-	
Lubricant type	:	Mobil Polyrex EM	

Notes

USABLE @208V 27.0A SF 1.00 SFA 27.0A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	16/05/2022			

Page 1 / 4
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 13180570



Performance : 230/460 V 60 Hz 4P

Rated current : 24.4/12.2 A
 LRC : 7.0
 Rated torque : 4.12 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 300 %
 Rated speed : 1760 rpm

Moment of inertia (J) : 0.0451 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 4	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 13180570



Performance : 190/380 V 50 Hz 4P

Rated current : 22.4/11.2 A
LRC : 7.6
Rated torque : 3.72 kgfm
Locked rotor torque : 250 %
Breakdown torque : 320 %
Rated speed : 1465 rpm

Moment of inertia (J) : 0.0451 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 4		
Checked by				
Date	16/05/2022			
		Revision		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 13180570





Performance : 220/415 V 50 Hz 4P

Rated current : 20.8/11.0 A
LRC : 8.3
Rated torque : 3.70 kgfm
Locked rotor torque : 290 %
Breakdown torque : 360 %
Rated speed : 1470 rpm

Moment of inertia (J) : 0.0451 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 4	Revision
Checked by					
Date	16/05/2022				



Color Munsell N 1 matte black									
Painting plan 207N									
Mounting B34D									
						HYBRISUSER			00
ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE VER
EXECUTED	HYBRISUSER	 THREE PH. MOTOR ROLLED STEEL JM NEMA PREM. EFF. FRAME 213/5JM IP55 TEFC				PREVIEW			
CHECKED									
RELEASED									
REL. DATE		WMO	Jaragua do Sul	Product Engineering	SHEET	1	/	1	