DATA SHEET

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : Wjet Pump Single-Phase Start Capacitor

Product code : 10084016

Frame	: W56J	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 0.5 HP (0.37 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 9.30/3.90-4.65 A	Protection degree	: IP21
L. R. Amperes	: 42.8/17.9-21.4 A	Cooling method	: IC01 - ODP
LRC	: 4.6x(Code L)	Mounting	: F-1
No load current	: 7.10/3.06-3.55 A	Rotation¹	: CCW
Rated speed	: 3465 rpm	Starting method	: Direct On Line
Slip	: 3.75 %	Approx. weight³	: 9.0 kg
Rated torque	: 0.105 kgfm		
Locked rotor torque	: 190 %		
Breakdown torque	: 290 %		
Insulation class	: B		
Service factor	: 1.60		
Moment of inertia (J)	: 0.0080 kgm²		

Output	50%	75%	100%
Efficiency (%)	44.8	53.5	58.0
Power Factor	0.47	0.55	0.63

Foundation loads

Max. traction	: 5 kgf
Max. compression	: 14 kgf

		Drive end	Non drive end
Bearing type	:	6203 2RS	6202 2RS
Sealing	:	Slinger	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	24/10/2024		1 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: Wjet Pump Single-Phase Start Capacitor	Product code :	10084016





Performance	: 115/208-230 V 60 Hz 2P		
Rated current	: 9.30/3.90-4.65 A	Moment of inertia (J)	: 0.0080 kgm²
LRC	: 4.6	Duty cycle	: Cont.(S1)
Rated torque	: 0.105 kgfm	Insulation class	: B
Locked rotor torque	: 190 %	Service factor	:
Breakdown torque	: 290 %	Temperature rise	: 80 K
Rated speed	: 3465 rpm		


Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	24/10/2024		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice







Mounting B14R(D)

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER	SINGLE PH. MOTOR WJET PUMP	PREVIEW		
CHECKED		FRAME W56J IP21 ODP	WDD	00	
RELEASED					
REL. DATE		WMO Jaragua do Sul Product Engineering	SHEET	1 / 1	

1/2 HP 02 Poles 60 Hz

A

Dimensions in inches

XME A3

WEG's property. Forbidden reproduction without previous authorization.