DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line	: W22 Close Coupled Pump JP NEMA Premium Efficiency Three-Phase	Product code :	15858654

Frame	: 213/5JP	Locked rotor time	: 21s (cold) 12s (hot)
Output	: 15 HP (11 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 13.6 A	Protection degree	: IP55
L. R. Amperes	: 107 A	Cooling method	: IC411 - TEFC
LRC	: 7.9x(Code J)	Mounting	: F-1
No load current	: 4.64 A	Rotation[1]	: Both (CW and CCW)
Rated speed	: 3520 rpm	Noise level[2]	: 68.0 dB(A)
Slip	: 2.22 %	Starting method	: Direct On Line
Rated torque	: 3.09 kgfm	Approx. weight[3]	: 82.0 kg
Locked rotor torque	: 240 %		
Breakdown torque	: 280 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0268 kgm²		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	0.000	90.2	91.0	91.0
Power Factor	0.00	0.76	0.85	0.89

Foundation loads

Max. traction	: 119 kgf
Max. compression	: 201 kgf

		Drive end	Non drive end
Bearing type	:	6309 Z C3	6207 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	19000 h	0 h
Lubricant amount	:	13 g	0 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	24/10/2024		1 / 2	


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: W22 Close Coupled Pump JP NEMA Premium Efficiency Three-Phase	Product code :	15858654




Performance	: 575 V 60 Hz 2P


Rated current	: 13.6 A	Moment of inertia (J)	: 0.0268 kgm²
LRC	: 7.9	Duty cycle	: Cont.(S1)
Rated torque	: 3.09 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.25
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 3520 rpm	Design	: B


Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	24/10/2024		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice










DE Shaft End



EUNC 1/2"-13 WEG WPR-7309

Design B
Color RAL 5009
Painting plan 207A
Mounting NEMA F-1
Mounting B34R(D)

15 HP 02 Poles 60 Hz | A

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER
CHECKED	
RELEASED	
REL. DATE	

THREE PH. MOTOR JM/JP/JET PUMP W22 NEMA PREM. EFF.
FRAME 213/5JP IP55 TEFC

PREVIEW

WDD 00

SHEET /

Dimensions in inches

A3

WEG's property. Forbidden reproduction without previous authorization.