

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Jet Pump - J type Three-Phase Product code : 13721750

Frame	: W56J	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: W-6
Duty cycle	: Cont.(S1)	Rotation ¹	: CCW
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 7.9 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0008 kgm ²

Output [HP]	0.5	0.5	0.5
Poles	2	2	2
Frequency [Hz]	60	50	50
Rated voltage [V]	208-230/460	190/380	220/415
Rated current [A]	1.73-1.57/0.784	1.77/0.885	1.58/0.836
L. R. Amperes [A]	13.3-12.1/6.04	10.3/5.13	10.7/5.68
LRC [A]	7.7x(Code L)	5.8x(Code H)	6.8x(Code K)
No load current [A]	0.719-0.834/0.417	0.816/0.408	0.879/0.466
Rated speed [RPM]	3435	2780	2825
Slip [%]	4.58	7.33	5.83
Rated torque [kgfm]	0.106	0.131	0.128
Locked rotor torque [%]	330	240	300
Breakdown torque [%]	360	250	310
Service factor		1.15	1.15
Temperature rise	80 K	80 K	80 K
Locked rotor time	32s (cold) 18s (hot)	32s (cold) 18s (hot)	25s (cold) 14s (hot)
Noise level ²	65.0 dB(A)	64.0 dB(A)	64.0 dB(A)
Efficiency (%)	25%		
	50%	68.0	72.0
	75%	72.0	75.0
	100%	74.0	74.7
Power Factor	25%		
	50%	0.64	0.70
	75%	0.75	0.81
	100%	0.80	0.85

Bearing type Sealing Lubrication interval Lubricant amount Lubricant type	Drive end	Non drive end	Foundation loads Max. traction : 8 kgf Max. compression : 16 kgf
	6203 2RS	6202 2RS	
	V'Ring	V'Ring	
	-	-	
	-	-	
	Mobil Polyrex EM		

Notes
USABLE @208V SF 1.00

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 4 Revision		
Checked by				
Date	16/05/2022			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Jet Pump - J type Three-Phase

Product code : 13721750



Performance : 208-230/460 V 60 Hz 2P

Rated current : 1.73-1.57/0.784 A
 LRC : 7.7
 Rated torque : 0.106 kgfm
 Locked rotor torque : 330 %
 Breakdown torque : 360 %
 Rated speed : 3435 rpm

Moment of inertia (J) : 0.0008 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 4	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Jet Pump - J type Three-Phase

Product code : 13721750



Performance : 190/380 V 50 Hz 2P

Rated current : 1.77/0.885 A
 LRC : 5.8
 Rated torque : 0.131 kgfm
 Locked rotor torque : 240 %
 Breakdown torque : 250 %
 Rated speed : 2780 rpm

Moment of inertia (J) : 0.0008 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 4	Revision
Checked by					
Date	16/05/2022				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Jet Pump - J type Three-Phase

Product code : 13721750



Performance : 220/415 V 50 Hz 2P

Rated current : 1.58/0.836 A
LRC : 6.8
Rated torque : 0.128 kgfm
Locked rotor torque : 300 %
Breakdown torque : 310 %
Rated speed : 2825 rpm

Moment of inertia (J) : 0.0008 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 4 / 4Revision		
Checked by				
Date	16/05/2022			

