DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Brake Motor NEMA Premium Efficiency Three-Phase

Product code : 15808380

Frame	: 284/6T
Output	: 15 HP (11 kW)
Poles	: 6
Frequency	: 60 Hz
Rated voltage	: 575 V
Rated current	: 14.3 A
L. R. Amperes	: 91.6 A
LRC	: 6.4x(Code G)
No load current	: 5.60 A
Rated speed	: 1175 rpm
Slip	: 2.08 %
Rated torque	: 9.26 kgfm
Locked rotor torque	: 229 %
Breakdown torque	: 260 %
Insulation class	: F
Service factor	: 1.25
Moment of inertia (J)	: 0.3310 kgm²
Design	: B

Locked rotor time	: 36s (cold) 20s (hot)
Temperature rise	: 80 K
Duty cycle	: Cont.(S1)
Ambient temperature	: -20°C to +40°C
Altitude	: 1000 m.a.s.l.
Protection degree	: IP55
Cooling method	: IC411 - TEFC
Mounting	: F-1
Rotation¹	: Both (CW and CCW)
Noise level²	: 59.0 dB(A)
Starting method	: Direct On Line
Approx. weight³	: 221 kg

Output	50%	75%	100%
Efficiency (%)	91.0	91.7	91.7
Power Factor	0.69	0.80	0.84

Foundation loads

Max. traction	: 234 kgf
Max. compression	: 455 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
8.9	7.6	7.0	4.1	2.8	1.8	1.2

		Drive end	Non drive end
Bearing type	:	6311 C3	6211 C3
Sealing	:	V'Ring	Lip Seal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	18 g	11 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	23/10/2023		1 / 3	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Brake information

Voltage: 525-575 V
Brake Torque: 26.5 kgfm

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	23/10/2023		2 / 3	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Brake Motor NEMA Premium Efficiency Three-Phase

Product code : 15808380





Performance	: 575 V 60 Hz 6P		
Rated current	: 14.3 A	Moment of inertia (J)	: 0.3310 kgm²
LRC	: 6.4	Duty cycle	: Cont.(S1)
Rated torque	: 9.26 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.25
Breakdown torque	: 260 %	Temperature rise	: 80 K
Rated speed	: 1175 rpm	Design	: B


Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	23/10/2023		3 / 3	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice








Brake voltage 525-575 V
Brake 20 (260 Nm)
Color RAL 5009
Painting plan 203A
Mounting NEMA F-1
Mounting B3R(D)

DE Shaft End



15 HP 06 Poles 60 Hz | A

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER
CHECKED	
RELEASED	
REL. DATE	

THREE PH. MOTOR W22 BRAKE MOTOR NEMA PREM. EFF.
FRAME 284/6T IP55 TEFC

PREVIEW

WDD | 00

SHEET /

Dimensions in inches

A3

WEG's property. Forbidden reproduction without previous authorization.