

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Multimounting IE3 Three-Phase Product code : 11728462

Frame	: 112M	Locked rotor time	: 34s (cold) 19s (hot)
Output	: 5.5 HP (4 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 5.82 A	Protection degree	: IP55
L. R. Amperes	: 46.6 A	Cooling method	: IC411 - TEFC
LRC	: 8.0	Mounting	: B3L(E)
No load current	: 3.40 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1755 rpm	Noise level ²	: 56.0 dB(A)
Slip	: 2.50 %	Starting method	: Direct On Line
Rated torque	: 2.27 kgfm	Approx. weight ³	: 40.0 kg
Locked rotor torque	: 250 %		
Breakdown torque	: 350 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0182 kgm ²		
Design	: N		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	87.5	89.5	89.5	Max. traction	: 147 kgf
Power Factor	0.58	0.70	0.77	Max. compression	: 187 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.2	9.4	9.2	6.3	4.5	3.4	2.6

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6307 ZZ	6206 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	25/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Multimounting IE3 Three-Phase

Product code : 11728462



Performance : 575 V 60 Hz 4P

Rated current : 5.82 A
LRC : 8.0
Rated torque : 2.27 kgfm
Locked rotor torque : 250 %
Breakdown torque : 350 %
Rated speed : 1755 rpm

Moment of inertia (J) : 0.0182 kgm²
Duty cycle : S1
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : N

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					

