

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Product code : 19225689

Frame	: 184HP	Locked rotor time	: 20 s (hot) 36 s (cold)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 3280 ft
Rated current	: 4.72 A	Protection degree	: IP55
L. R. Amperes	: 35.9 A	Cooling method	: IC411 - TEFC
LRC	: 7.6	Mounting	: W-6
No load current	: 1.40 A	Rotation ¹	: Both
Rated speed	: 3475 rpm	Noise level ²	: 66.0 dB(A)
Slip	: 3.47 %	Vibration class	: A
Rated torque	: 7.52 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 200.0 %	Coupling	: Direct
Pull up torque	: 170.0 %	Approx. weight ³	: 95.5 lb
Breakdown torque	: 290.0 %	Painting plan	: 207A
Insulation class	: F	Color	: RAL 5009
Service factor	: 1.25	Design	: B
Moment of inertia (J)	: 0.1614 sq.ft.lb		

Output	50%	75%	100%
Efficiency (%)	87.3	88.5	88.5
Power Factor	0.79	0.86	0.89

Load type	: -
Load torque	: -
Load inertia (J=GD ² /4)	: -

	Drive end	Non drive end
Bearing type #1	6308-ZZ	6206-ZZ
Bearing type #2	-	-
Lubrication interval	-	-
Lubricant amount #1	-	-
Lubricant amount #2	-	-
Lubricant type	MOBIL POLYREX EM	

Foundation loads	
Max. traction	:
Max. compression	:

Notes

See notes on page 2.

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
12.4	10.0	9.2	6.0	3.6	2.2	1.4

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary			Rev.	Checked	Date
Performed by	farazq				1871047529	
Checked by	AUTOMATICO				Page	Rev.
Date	08/07/2026				1 / 2	0



Three Phase Induction Motor - Squirrel Cage



Product code : 19225689

VT 1000:1, CT 20:1, 1.00SF - T4A

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7	
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12	
	Noise	: MG1 - Part 9			
	This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight, subject to be changed after manufacturing process.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.		
Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1871047529	
Checked by	AUTOMATICO			Page	Rev.
Date	08/07/2026			2 / 2	0

Dimensions in inches