

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :				
Product line : Single-Phase		Product code : 13637399		
Frame : 56HC	Insulation class : F	Cooling method : IC01 - ODP	Mounting : F-1	
Duty cycle : Cont.(S1)	Ambient temperature : -20°C to +40°C	Rotation ¹ : Both (CW and CCW)	Starting method : Direct On Line	
Altitude : 1000 m.a.s.l.	Design : L	Approx. weight ³ : 21.2 kg	Moment of inertia (J) : 0.0036 kgm ²	
Output [HP]	3			
Poles	2			
Frequency [Hz]	60			
Rated voltage [V]	115/208-230			
Rated current [A]	26.4/14.6-13.2			
L. R. Amperes [A]	211/117-106			
LRC [A]	8.0x(Code H)			
No load current [A]	9.00/3.88-4.50			
Rated speed [RPM]	3485			
Slip [%]	3.19			
Rated torque [kgfm]	0.625			
Locked rotor torque [%]	200			
Breakdown torque [%]	250			
Service factor				
Temperature rise	80 K			
Locked rotor time	10s (cold) 6s (hot)			
Noise level ²	58.0 dB(A)			
Efficiency (%)	25%			
	50%	71.0		
	75%	76.0		
	100%	78.0		
Power Factor	25%			
	50%	0.85		
	75%	0.91		
	100%	0.93		
Bearing type : 6204 ZZ	Drive end	Non drive end	Foundation loads	
Sealing : Without			Max. traction : 39 kgf	
	Bearing Seal	Bearing Seal	Max. compression : 60 kgf	
Lubrication interval : -	-	-		
Lubricant amount : -	-	-		
Lubricant type : Mobil Polyrex EM				
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.	
Rev.	Changes Summary		Performed	Checked
Performed by				
Checked by			Page	Revision
Date	17/05/2022		1 / 2	

LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Single-Phase

Product code : 13637399




Performance : 115/208-230 V 60 Hz 2P

Rated current : 26.4/14.6-13.2 A
 LRC : 8.0
 Rated torque : 0.625 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 250 %
 Rated speed : 3485 rpm

Moment of inertia (J) : 0.0036 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 80 K
 Design : L

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					



Color Munsell N 1 matte black									
Painting plan 207N									
Mounting B34D									
				HYBRISUSER					00
ECM	LOC	SUMMARY OF MODIFICATIONS			EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER		SINGLE PH. MOTOR ROLLED STEEL FRAME 56HC IP21 ODP			PREVIEW WDD 00			
CHECKED									
RELEASED									
REL. DATE		WMO	Jaragua do Sul	Product Engineering	SHEET	1 / 1			