

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 17371727

Frame	: 586/7TZ	Locked rotor time	: 45s (cold) 25s (hot)
Output	: 500 HP (370 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 575 V	Ambient temperature	: -20°C to +40°C
Poles	: 6	Altitude	: 1000 m.a.s.l.
Rated current	: 482 A	Protection degree	: IP55
	: 6.0x(Code G)	Cooling method	: IC411 - TEFC
Rated speed	: 1192 rpm	Mounting	: F-1
Rated torque	: 304 kgfm	Rotation ¹	: Both (CW and CCW)
Insulation class	: F	Noise level ²	: 77.0 dB(A)
Service factor	: 1.15	Starting method	: Direct On Line
Moment of inertia (J)	: 15.5 kgm ²	Approx. weight ³	: 2145 kg

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.8	96.2	96.2	Max. traction	: 3304 kgf
Power Factor	0.66	0.76	0.80	Max. compression	: 5449 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.6	3.5	2.8	2.8	1.9	1.5	0.8

		Drive end	Non drive end
Bearing type	:	NU-324 C3	6319 C3
Sealing	:	Taconite Labyrinth	Taconite Labyrinth
Lubrication interval	:	6000 h	13000 h
Lubricant amount	:	72 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 3		
Checked by				
Date	28/05/2026			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 3	
Date	28/05/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 17371727



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	28/05/2026				
				Page 3 / 3	Revision

