DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line	: W22 NEMA Premium Efficiency Three-Phase	Product code :	13500649

Frame	: 586/7TZ	Locked rotor time	: 63s (cold) 35s (hot)
Output	: 300 HP (220 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 575 V	Ambient temperature	: -20°C to +40°C
Poles	: 4	Altitude	: 1000 m.a.s.l.
Rated current	: 280 A	Protection degree	: IP55
	: 7.2x(Code H)	Cooling method	: IC411 - TEFC
Rated speed	: 1791 rpm	Mounting	: F-1
Rated torque	: 122 kgfm	Rotation[1]	: Both (CW and CCW)
Insulation class	: F	Noise level[2]	: 78.0 dB(A)
Service factor	: 1.15	Starting method	: Direct On Line
Moment of inertia (J)	: 5.92 kgm²	Approx. weight[3]	: 1397 kg
Design	: A		

Output	25%	50%	75%	100%
Efficiency (%)	0.000	95.4	95.8	96.2
Power Factor	0.00	0.70	0.80	0.82

Foundation loads

Max. traction	: 1465 kgf
Max. compression	: 2862 kgf

		Drive end	Non drive end
Bearing type	:	NU-324 C3	6319 C3
Sealing	:	Taconite Labyrinth	Taconite Labyrinth
Lubrication interval	:	3000 h	8000 h
Lubricant amount	:	72 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes
W22 Crusher Duty - NEMA Premium Efficiency

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	28/05/2026		1 / 3	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 ºC

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	28/05/2026		2 / 3	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 13500649



Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	28/05/2026		3 / 3	


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

EIXO/SHAFT	
PADRÃO/STANDARD	
OPCIONAL/OPTIONAL	
ESPECIAL/SPECIAL	X


Dimensões em polegada
Dimensions in inches


CERTIFIED
WEG MOTORES
Certified document.
Not subject to changes.

THIS IS AN UPDATED REVISION, THE PREVIOUS ONE MUST BE DISREGARDED.





Main terminal box





Fixar o conduíte no suporte com abraçadeiras.
Fasten the conduit on support with cables ties.





DE Shaft End

500 HP	04 Poles	60Hz		J
500 HP	06 Poles	60Hz		I
450 HP	04 Poles	60Hz		H
450 HP	06 Poles	60Hz		G
400 HP	04 Poles	60Hz		F
400 HP	06 Poles	60Hz		E
350 HP	04 Poles	60Hz		D
350 HP	06 Poles	60Hz		C
300 HP	04 Poles	60Hz		B
300 HP	06 Poles	60Hz	414149741/0 MEC	A

Rolamento dianteiro de rolos / DE roller bearing
Proteção térmica para desligamento – termostato 155°C Thermal protection to switch off – thermostat 155°C
Dispositivo de travamento de eixo / Shaft locking device
Linha do motor: Crusher Duty / Motor purpose: Crusher Duty
Tampa dianteira especial / Special DE endshield
Rolamento dianteiro de rolos NU–324 / NU–324 DE roller bearing
Tampa traseira com mancal eletricamente isolado NDE endshield with electrically insulated bearing hub
Cor RAL 5009 / Color RAL 5009
Plano de pintura 203A / Painting plan 203A
Forma construtiva NEMA F–1 / Mounting NEMA F–1
Forma construtiva B3D / Mounting B3R(D)

WEG ELECTRIC CORPORATION - WEC

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
500001929025		RETIRADO NOTA - SOL PLACAS	FRANCINES	JACKSONHM	JACKSONHM	30.04.2021	06
500001331189		ADIC.NOTA CONDUITE/ADD NOTE CONDUIT	MENSOR	EANJOS	EANJOS	05.07.2017	05

EXECUTED	DVEGINI
CHECKED	NSCHMIDT
RELEASED	NSCHMIDT
REL DT	25.01.2016

THREE PHASE W22 MOTOR - NEMA PREMIUM EFF
FRAME 586/7TZ IP55

WMO Jaragua do Sul Product Engineering

10004040391
000 | 06

SHEET 1 / 1

UNCONTROLLED COPY
RELEASED
ZME A3

WEG's property. Forbidden reproduction without previous authorization.