

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W22 Cooling Tower - TEFC - NEMA Premium
Efficiency

Frame	: 213/5T	Locked rotor time	: 58 s (hot) 104 s (cold)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 3280 ft
Rated current	: 3.53 A	Protection degree	: IP55
L. R. Amperes	: 24.7 A	Cooling method	: IC418 - TEAO
LRC	: 7.0	Minimum air speed over motor	: 8.2 m/s
No load current	: 2.04 A	Mounting	: F-2
Rated speed	: 1175 rpm	Rotation ¹	: Both
Slip	: 2.08 %	Noise level ²	: 55.0 dB(A)
Rated torque	: 13.2 ft.lb	Vibration class	: A
Locked rotor torque	: 190 %	Starting method	: Direct On Line
Pull up torque	: 160 %	Coupling	: Direct
Breakdown torque	: 270 %	Approx. weight ³	: 149 lb
Insulation class	: F	Painting plan	: 202E
Service factor	: 1.25	Color	: RAL 5009
Moment of inertia (J)	: 1.20 sq.ft.lb	Design	: B

Output	50%	75%	100%
Efficiency (%)	86.5	88.5	89.5
Power Factor	0.50	0.63	0.70

Load type	: -
Load torque	: -
Load inertia (J=GD ² /4)	: -

	Drive end	Non drive end
Bearing type #1	6308-2RS	6207-2RS
Bearing type #2	-	-
Lubrication interval	-	-
Lubricant amount #1	-	-
Lubricant amount #2	-	-
Lubricant type	POLYUREA BASED GREASE	

Foundation loads	
Max. traction	: 565 N
Max. compression	: 1229 N

Notes

See notes on page 2.

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.0	8.6	8.0	6.6	4.3	3.4	2.4

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary			Rev.	Checked	Date
Performed by	farazq				1868615243	
Checked by	AUTOMATICO				Page	Rev.
Date	02/07/2026				1 / 2	0

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W22 Cooling Tower - TEFC - NEMA Premium Efficiency

Space heater information
Voltage: 110-127/200-240 V
Output: 25-33/21-30 W

Notes

Customer information
CSA
Class I, Div 2, Gr A, B, C, D, 1.15SF - T3
Class I, Zone 2, IIC, 1.15SF - T3
Class II, Div 2, Gr F, G - T4
For use on PWM: Gr. A, B, C, D, F,
VT 1000:1, CT 20:1, 1.00SF - T3

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.

(1) Looking the motor from the shaft end.

(2) Measured at 1m and with tolerance of +3dB(A).

(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1868615243	
Checked by	AUTOMATICO			Page	Rev.
Date	02/07/2026			2 / 2	0

