

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP Compressor Duty Standard Efficiency Product code : 17544537

Frame	: W56	Locked rotor time	: 11 s (hot) 20 s (cold)
Output	: 0.75 HP (0.55 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 115/208-230 V	Altitude	: 3280 ft
Rated current	: 11.3/5.70-5.67 A	Protection degree	: IP21
L. R. Amperes	: 65.8/33.1-32.9 A	Cooling method	: IC01 - ODP
LRC	: 5.8	Mounting	: F-1/B3R(D)
No load current	: 9.80/4.22-4.90 A	Rotation ¹	: Both
Rated speed	: 3455 rpm	Noise level ²	: 70.0 dB(A)
Slip	: 4.03 %	Vibration class	: A
Rated torque	: 1.12 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 180 %	Approx. weight ³	: 22.1 lb
Pull up torque	: 150 %	Painting plan	: 207N
Breakdown torque	: 230 %	Color	: MUNSELL N 1 - MATTE
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 0.0190 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	52.0	60.0	63.0	Load torque	: -
Power Factor	0.47	0.58	0.67	Load inertia (J=GD ² /4)	: -

	Drive end	Non drive end	Foundation loads	
Bearing type	6203-ZZ	6202-ZZ	Max. traction	: -
Lubrication interval	-	-	Max. compression	: -
Lubricant amount	-	-		
Lubricant type	MOBIL POLYREX EM			

Notes

See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq		1847446794		
Checked by	AUTOMATICO		Page	Rev.	
Date	12/05/2026		1 / 2	0	

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP Compressor Duty Standard Efficiency Product code : 17544537

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight, subject to be changed after manufacturing process.	These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.
---	---

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1847446794	
Checked by	AUTOMATICO			Page	Rev.
Date	12/05/2026			2 / 2	0

