

# DATA SHEET

## Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP Compressor Duty Standard Efficiency Product code : 17407307

|                       |                    |                             |                        |
|-----------------------|--------------------|-----------------------------|------------------------|
| Frame                 | : 56H              | Locked rotor time           | : 5 s (hot) 9 s (cold) |
| Output                | : 2 HP (1.5 kW)    | Temperature rise            | : 80 K                 |
| Poles                 | : 2                | Duty cycle                  | : S1                   |
| Frequency             | : 60 Hz            | Ambient temperature         | : -20 °C to +40 °C     |
| Rated voltage         | : 115/208-230 V    | Altitude                    | : 3280 ft              |
| Rated current         | : 19.8/10.2-9.88 A | Protection degree           | : IP21                 |
| L. R. Amperes         | : 123/62.9-61.3 A  | Cooling method              | : IC01 - ODP           |
| LRC                   | : 6.2              | Mounting                    | : F-1/B3R(D)           |
| No load current       | : 14.2/6.12-7.10 A | Rotation <sup>1</sup>       | : Both                 |
| Rated speed           | : 3480 rpm         | Noise level <sup>2</sup>    | : 70.0 dB(A)           |
| Slip                  | : 3.33 %           | Vibration class             | : A                    |
| Rated torque          | : 2.97 ft.lb       | Starting method             | : Direct On Line       |
| Locked rotor torque   | : 180 %            | Approx. weight <sup>3</sup> | : 28.7 lb              |
| Pull up torque        | : 150 %            | Painting plan               | : 207N                 |
| Breakdown torque      | : 220 %            | Color                       | : MUNSELL N 1 - MATTE  |
| Insulation class      | : F                |                             |                        |
| Service factor        | : 1.00             |                             |                        |
| Moment of inertia (J) | : 0.0380 sq.ft.lb  |                             |                        |

|                |      |      |      |                                     |     |
|----------------|------|------|------|-------------------------------------|-----|
| Output         | 50%  | 75%  | 100% | Load type                           | : - |
| Efficiency (%) | 60.0 | 69.8 | 75.0 | Load torque                         | : - |
| Power Factor   | 0.67 | 0.78 | 0.86 | Load inertia (J=GD <sup>2</sup> /4) | : - |

|                      |                  |               |                  |     |
|----------------------|------------------|---------------|------------------|-----|
|                      | Drive end        | Non drive end | Foundation loads |     |
| Bearing type         | 6204-ZZ          | 6202-ZZ       | Max. traction    | : - |
| Lubrication interval | -                | -             | Max. compression | : - |
| Lubricant amount     | -                | -             |                  |     |
| Lubricant type       | MOBIL POLYREX EM |               |                  |     |

### Notes

See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

| Rev.         | Changes Summary |  | Rev.       | Checked | Date |
|--------------|-----------------|--|------------|---------|------|
|              |                 |  |            |         |      |
| Performed by | farazq          |  | 1847547472 |         |      |
| Checked by   | AUTOMATICO      |  | Page       | Rev.    |      |
| Date         | 12/05/2026      |  | 1 / 2      | 0       |      |

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP Compressor Duty Standard Efficiency Product code : 17407307



| Thermal protection ID | Application | Type | Quantity | Sensing Temperature |
|-----------------------|-------------|------|----------|---------------------|
|-----------------------|-------------|------|----------|---------------------|


Notes

|           |               |                 |           |                 |
|-----------|---------------|-----------------|-----------|-----------------|
| Standards | Specification | : MG1 - Part 10 | Vibration | : MG1 - Part 7  |
|           | Test          | : MG1 - Part 12 | Tolerance | : MG1 - Part 12 |
|           | Noise         | : MG1 - Part 9  |           |                 |

|                                                                                                                                                                                                                                                               |                                                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| This revision replaces and cancel the previous one, which must be eliminated.<br>(1) Looking the motor from the shaft end.<br>(2) Measured at 1m and with tolerance of +3dB(A).<br>(3) Approximate weight, subject to be changed after manufacturing process. | These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12. |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|

|              |                 |  |            |         |      |
|--------------|-----------------|--|------------|---------|------|
| Rev.         | Changes Summary |  | Rev.       | Checked | Date |
| Performed by | farazq          |  | 1847547472 |         |      |
| Checked by   | AUTOMATICO      |  | Page       | Rev.    |      |
| Date         | 12/05/2026      |  | 2 / 2      | 0       |      |



|                         |            |                                                                                       |                                                            |  |  |                                            |         |                                                                                       |      |     |
|-------------------------|------------|---------------------------------------------------------------------------------------|------------------------------------------------------------|--|--|--------------------------------------------|---------|---------------------------------------------------------------------------------------|------|-----|
| 2 HP   02 Poles   60 Hz |            |                                                                                       |                                                            |  |  |                                            |         |                                                                                       |      | A   |
|                         |            |                                                                                       |                                                            |  |  |                                            |         |                                                                                       |      |     |
|                         |            |                                                                                       |                                                            |  |  | Scale                      2 : 7           |         |                                                                                       |      |     |
|                         |            |                                                                                       |                                                            |  |  |                                            |         |                                                                                       |      |     |
|                         |            |                                                                                       |                                                            |  |  | HYBRISUSER                                 |         |                                                                                       |      | 00  |
| ECM                     | LOC        | SUMMARY OF MODIFICATIONS                                                              |                                                            |  |  | EXECUTED                                   | CHECKED | RELEASED                                                                              | DATE | VER |
| EXECUTED                | HYBRISUSER |  | SINGLE PH. MOTOR W01 COMPRESSOR DUTY<br>FRAME 56H IP21 ODP |  |  | PREVIEW<br><br>WDD                      00 |         |  |      |     |
| CHECKED                 |            |                                                                                       |                                                            |  |  |                                            |         |                                                                                       |      |     |
| RELEASED                |            |                                                                                       |                                                            |  |  |                                            |         |                                                                                       |      |     |
| REL. DATE               |            |                                                                                       |                                                            |  |  |                                            |         |                                                                                       |      |     |
|                         |            |                                                                                       |                                                            |  |  | SHEET                                      |         | 1 / 1                                                                                 |      |     |