# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage

| | |
|---|---|
| Customer | : |

| | | | |
|---|---|---|---|
| Product line | : Premium Efficiency Three-Phase | Product code : | 13500356 |

| | | | |
|---|---|---|---|
| Frame | : 56C | Cooling method | : IC411 - TEFC |
| Insulation class | : F | Mounting | : F-1 |
| Duty cycle | : Cont.(S1) | Rotation[1] | : Both (CW and CCW) |
| Ambient temperature | : -20°C to +40°C | Starting method | : Direct On Line |
| Altitude | : 1000 m.a.s.l. | Approx. weight[3] | : 14.9 kg |
| Protection degree | : IP55 | Moment of inertia (J) | : 0.0043 kgm² |
| Design | : B | | |

| | | |
|---|---|---|
| Output [HP] | | 1.5 |
| Poles | | 2 |
| Frequency [Hz] | | 60 |
| Rated voltage [V] | | 575 |
| Rated current [A] | | 1.50 |
| L. R. Amperes [A] | | 13.6 |
| LRC [A] | | 9.1x(Code L) |
| No load current [A] | | 0.687 |
| Rated speed [RPM] | | 3520 |
| Slip [%] | | 2.22 |
| Rated torque [kgfm] | | 0.309 |
| Locked rotor torque [%] | | 229 |
| Breakdown torque [%] | | 300 |
| Service factor | | 1.15 |
| Temperature rise | | 80 K |
| Locked rotor time | | 30s (cold) 17s (hot) |
| Noise level[2] | | 68.0 dB(A) |
| Efficiency (%) | 25% | |
| | 50% | 80.0 |
| | 75% | 82.5 |
| | 100% | 84.0 |
| Power Factor | 25% | |
| | 50% | 0.71 |
| | 75% | 0.82 |
| | 100% | 0.88 |

| | | Drive end | Non drive end |
|---|---|---|---|
| Bearing type | : | 6204 ZZ | 6202 ZZ |
| Sealing | : | V'Ring | Without Bearing Seal |
| Lubrication interval | : | - | - |
| Lubricant amount | : | - | - |
| Lubricant type | : | Mobil Polyrex EM | |

Foundation loads

Max. traction : 22 kgf

Max. compression : 37 kgf

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |


| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 11/05/2022 | | 1 / 2 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage

| | | | |
|---|---|---|---|
| Customer | : | | |
| Product line | : Premium Efficiency Three-Phase | Product code : | 13500356 |





| | | | |
|---|---|---|---|
| Performance | : 575 V 60 Hz 2P | | |
| Rated current | : 1.50 A | Moment of inertia (J) | : 0.0043 kgm² |
| LRC | : 9.1 | Duty cycle | : Cont.(S1) |
| Rated torque | : 0.309 kgfm | Insulation class | : F |
| Locked rotor torque | : 229 % | Service factor | : 1.15 |
| Breakdown torque | : 300 % | Temperature rise | : 80 K |
| Rated speed | : 3520 rpm | Design | : B |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 11/05/2022 | | 2 / 2 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice




Fan cover - steel plate

Color Munsell N 1 matte black

Painting plan 207N

Mounting B34D

| ECM | LOC | SUMMARY OF MODIFICATIONS | EXECUTED | CHECKED | RELEASED | DATE | VER |
|---|---|---|---|---|---|---|---|
| | | | HYBRISUSER | | | | 00 |

| | | | | | |
|---|---|---|---|---|---|
| EXECUTED | HYBRISUSER | THREE PH. MOTOR ROLLED STEEL PREM. EFF. | PREVIEW | | |
| CHECKED | | FRAME 56C IP55 TEFC | WDD | 00 | |
| RELEASED | | | | | |
| REL. DATE | | WMO Jaragua do Sul Product Engineering | SHEET | 1 / 1 | |

1.5 HP 02 Poles 60 Hz

A

Dimensions in inches

XME A3

WEG's property. Forbidden reproduction without previous authorization.