

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEAO - Grain Dryer

Product code : 18366731

Frame	: 182/4TZ	Cooling method	: IC418 - TEAO
Insulation class	: F	Minimum air speed over motor	: 16.8 m/s
Duty cycle	: S1	Mounting	: F-3/B3T
Ambient temperature	: -20 °C to +40 °C	Rotation ¹	: Both
Altitude	: 3280 ft	Starting method	: Direct On Line
Protection degree	: IP55	Approx. weight ³	: 0.0 lb
		Moment of inertia (J)	: 0.0000 sq.ft.lb

Output		7.5 HP (5.5 kW)	10 HP (7.5 kW)
Poles		2	2
Frequency		60 Hz	60 Hz
Rated voltage		230 V	230 V
Rated current		30.0 A	39.5 A
L. R. Amperes		315 A	316 A
LRC		10.5	8.0
No load current		12.3 A	12.3 A
Rated speed		3540 rpm	3490 rpm
Slip		1.67 %	3.06 %
Rated torque		11.0 ft.lb	14.8 ft.lb
Locked rotor torque		250 %	190 %
Pull up torque		210 %	160 %
Breakdown torque		470 %	340 %
Service factor		1.00	1.00
Temperature rise		105 K	105 K
Noise level ²		72.0 dB(A)	72.0 dB(A)
Locked rotor time (hot)		9 s	6 s
Locked rotor time (cold)		16 s	11 s
Efficiency (%)	50%	73.1	78.0
	75%	79.8	83.0
	100%	83.0	85.0
Power Factor	50%	0.92	0.94
	75%	0.95	0.96
	100%	0.96	0.97

	Drive end	Non drive end	Foundation loads
Bearing type	6206-ZZ	6205-ZZ	Max. traction : -
Lubrication interval	-	-	Max. compression : -
Lubricant amount	-	-	Load type : -
Lubricant type	MOBIL POLYREX EM		Load torque : -
			Load inertia (J=GD ² /4) : -

Notes

See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1847389405	
Checked by	AUTOMATICO			Page	Rev.
Date	12/05/2026			1 / 2	0

DATA SHEET


Single Phase Induction Motor - Squirrel Cage



Customer		: V.J. PAMENSKY CANADA INC.		
Product line		: W01 - TEAO - Grain Dryer	Product code : 18366731	
Thermal protection	ID	Application	Type	Quantity
	1	Winding	Thermostat - 2 wires	1 x Phase
				Sensing Temperature
				155°C

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight, subject to be changed after manufacturing process.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.	
Rev.	Changes Summary		Rev.	Checked
				Date
Performed by	farazq			1847389405
Checked by	AUTOMATICO			Page
Date	12/05/2026			2 / 2
				Rev.
				0



Center hole
EUNC 1/4"-20 WEG WPR-7309

UNCONTROLLED COPY

Dimensiones em pulgadas

RELEASED

ZME A3