DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line	: W22 NEMA Premium Efficiency Three-Phase	Product code :	13811912
		Catalog # :	

Frame	: 182/4T	Locked rotor time	: 45s (cold) 25s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 105 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.81/3.91 A	Protection degree	: IP55
L. R. Amperes	: 58.6/29.3 A	Cooling method	: IC410 - TENV
LRC	: 7.5x(Code J)	Mounting	: F-1
No load current	: 4.00/2.00 A	Rotation[1]	: Both (CW and CCW)
Rated speed	: 1750 rpm	Starting method	: VFD
Slip	: 2.78 %	Approx. weight[3]	: 90.4 lb
Rated torque	: 9.00 ft.lb		
Locked rotor torque	: 229 %		
Breakdown torque	: 340 %		
Insulation class	: H		
Service factor	: 1.00		
Moment of inertia (J)	: 0.3987 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	0.000	89.0	89.5	89.5
Power Factor	0.00	0.59	0.72	0.79

Foundation loads

Max. traction	: 150 lb
Max. compression	: 241 lb

		Drive end	Non drive end
Bearing type	:	6207 ZZ C3	6207 ZZ C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	0 h	0 h
Lubricant amount	:	0 g	0 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	06/03/2025		1 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 ºC

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	06/03/2025		2 / 2	


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


EJE/SHAFT	
ESTÁNDAR/STANDARD	
OPCIONAL/OPTIONAL	
ESPECIAL/SPECIAL	X


Dimensões em polegada
Dimensions in inches


PRELIMINARY DOCUMENT
Not to be used for installation purposes.

THIS IS AN UPDATED REVISION, THE PREVIOUS ONE MUST BE DISREGARDED.












NON DRIVE END





DRIVE END



MAIN TERMINAL BOX

Sin deflectora / Without fan cover
Termostato 155°C – Desconexión / Thermostats 155°C to trip
Sin ventilador / Without fan
Rodamiento esferas delantero ZZ–C3 / ZZ–C3 DE ball bearing
Anillo fijación del rodamiento / Bearing cap
Rodamiento esferas trasero ZZ–C3 / ZZ–C3 NDE ball bearing
Color RAL 5009 / Color RAL 5009
Plan de pintura 207A / Painting plan 207A
Forma constructiva NEMA F–1 / Mounting NEMA F–1
Forma constructiva B34D / Mounting B34R(D)

WEG ELECTRIC CORPORATION - WEC

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
500001952677		CONFORME A CLAIM 418290715	RESTELA	IRVINGI	IRVINGI	22.06.2021	02
500001241521		SE ACTUALIZAN DATOS ADICIONALES	OMARG	JOSE9	JOSE9	08.11.2016	01

OV: 4302353

EXECUTED	OLOPEZ	THREE PHASE W22 MOTOR - NEMA PREMIUM EFF	10004588365		
CHECKED	OMARG	FRAME 182/4TC IP55 TENV	000	02	
RELEASED	OMARG				
REL DT	03.11.2016	WMX Huehuetoca Product Engineering	SHEET	1 / 1	

3 HP 04 Poles 60Hz 414463438 A

UNCONTROLLED COPY
RELEASED
ZME A3

WEG's property. Forbidden reproduction without previous authorization.