

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Saw Arbor Motor Standard Efficiency Three-Phase Product code : 14301494

Frame	: 80S/MS	Locked rotor time	: 16s (cold) 9s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S6
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.43 A	Protection degree	: IP54
L. R. Amperes	: 25.1 A	Cooling method	: IC411 - TEFC
LRC	: 7.3	Mounting	: B3R(D)
No load current	: 1.65 A	Rotation ¹	: CCW
Rated speed	: 3500 rpm	Noise level ²	: 62.0 dB(A)
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 0.622 kgfm	Approx. weight ³	: 38.5 kg
Locked rotor torque	: 330 %		
Breakdown torque	: 370 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0032 kgm ²		
Design	: N		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	76.0	79.5	80.5	Max. traction	: 29 kgf
Power Factor	0.65	0.75	0.80	Max. compression	: 67 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6307 ZZ	6207 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	28/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Saw Arbor Motor Standard
Efficiency Three-Phase

Product code : 14301494




Performance : 575 V 60 Hz 2P

Rated current : 3.43 A
LRC : 7.3
Rated torque : 0.622 kgfm
Locked rotor torque : 330 %
Breakdown torque : 370 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0032 kgm²
Duty cycle : S6
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : N

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					



D										
E										
Counterclockwise rotation										
Color RAL 7022										
Painting plan 207A										
Mounting B3R(D)										

										A	
						HYBRISUSER				00	
ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE	VER	
EXECUTED	HYBRISUSER				THREE PH. MOTOR SAW ARBOR MOTOR FRAME 80S/MS IP54 TEFC			PREVIEW WDD 00			
CHECKED											
RELEASED											
REL. DATE											
			WMO	Jaragua do Sul	Product Engineering	SHEET		1 / 1			