DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line	: Saw Arbor Motor Standard Efficiency Three-Phase	Product code :	14381273

Frame	: 80M/MS	Locked rotor time	: 12s (cold) 7s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S6
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 5.32 A	Protection degree	: IP54
L. R. Amperes	: 42.5 A	Cooling method	: IC411 - TEFC
LRC	: 8.0	Mounting	: B3R(D)
No load current	: 2.30 A	Rotation[1]	: CCW
Rated speed	: 3470 rpm	Noise level[2]	: 62.0 dB(A)
Slip	: 3.61 %	Starting method	: Direct On Line
Rated torque	: 1.05 kgfm	Approx. weight[3]	: 45.0 kg
Locked rotor torque	: 340 %		
Breakdown torque	: 409 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0041 kgm²		
Design	: N		

Output	50%	75%	100%
Efficiency (%)	82.0	84.5	85.0
Power Factor	0.66	0.77	0.82

Foundation loads

Max. traction	: 67 kgf
Max. compression	: 112 kgf

		Drive end	Non drive end
Bearing type	:	6307 ZZ	6207 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	28/10/2024		1 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : Saw Arbor Motor Standard Efficiency Three-Phase

Product code : 14381273





Performance	: 575 V 60 Hz 2P		
Rated current	: 5.32 A	Moment of inertia (J)	: 0.0041 kgm²
LRC	: 8.0	Duty cycle	: S6
Rated torque	: 1.05 kgfm	Insulation class	: F
Locked rotor torque	: 340 %	Service factor	: 1.15
Breakdown torque	: 409 %	Temperature rise	: 80 K
Rated speed	: 3470 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	28/10/2024		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice





Counterclockwise rotation
Color RAL 7022
Painting plan 207A
Mounting B3R(D)

5 HP 02 Poles 60 Hz

A

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER	THREE PH. MOTOR SAW ARBOR MOTOR	PREVIEW
CHECKED		FRAME 80M/MS IP54 TEFC	WDD 00
RELEASED			
REL. DATE		WMO Jaragua do Sul Product Engineering	SHEET 1 / 1

Dimensions in mm

XME A3

WEG's property. Forbidden reproduction without previous authorization.