

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM
NEMA Premium Efficiency Three-Phase
Product code : 14495396

Frame : 213JM	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : F-3
Duty cycle : Cont.(S1)	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ² : 70.0 kg
Protection degree : IP55	Moment of inertia (J) : 0.0566 kgm ²
Design : B	

Output [HP]	7.5	7.5	7.5	7.5
Poles	4	4	4	4
Frequency [Hz]	60	50	50	50
Rated voltage [V]	230/460	380	400	415
Rated current [A]	18.4/9.18	11.0	10.6	10.4
L. R. Amperes [A]	130/65.2	61.4	65.7	69.3
LRC [A]	7.1x(Code H)	5.6x(Code F)	6.2x(Code G)	6.7x(Code H)
No load current [A]	7.80/3.90	3.90	4.10	4.40
Rated speed [RPM]	1765	1455	1460	1465
Slip [%]	1.94	3.00	2.67	2.33
Rated torque [kgfm]	3.08	3.74	3.73	3.72
Locked rotor torque [%]	220	180	190	210
Breakdown torque [%]	280	220	240	260
Service factor	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K
Locked rotor time	36s (cold) 20s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)
Noise level ²	58.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)
Efficiency (%)	25%			
	50%	89.5	89.5	89.5
	75%	91.0	89.5	90.2
	100%	91.7	89.6	90.2
Power Factor	25%			
	50%	0.66	0.72	0.69
	75%	0.76	0.81	0.78
	100%	0.82	0.85	0.83

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	10.2	10.3	10.2	10.7
	P2 (0,5;1,0)	9.0	9.1	9.0	9.5
	P3 (0,25;1,0)	8.4	8.5	8.5	8.9
	P4 (0,9;0,5)	4.8	4.9	4.8	5.1
	P5 (0,5;0,5)	3.6	3.6	3.6	3.7
	P6 (0,5;0,25)	2.4	2.4	2.4	2.5
	P7 (0,25;0,25)	1.7	1.8	1.7	1.8

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type :	6309 Z C3	6207 ZZ	Max. traction : 141 kgf
Sealing :	V'Ring	V'Ring	Max. compression : 216 kgf
Lubrication interval :	20000 h	40000 h	
Lubricant amount :	13 g	0 g	
Lubricant type :	Mobil Polyrex EM		

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/07/2026			

Page 1 / 6
Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 19.9A SF 1.15 SFA 22.9A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 6		Revision
Checked by					
Date	28/07/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM
NEMA Premium Efficiency Three-Phase

Product code : 14495396



Performance : 230/460 V 60 Hz 4P

Rated current : 18.4/9.18 A
LRC : 7.1
Rated torque : 3.08 kgfm
Locked rotor torque : 220 %
Breakdown torque : 280 %
Rated speed : 1765 rpm

Moment of inertia (J) : 0.0566 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	28/07/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM
NEMA Premium Efficiency Three-
Phase

Product code : 14495396



Performance : 380 V 50 Hz 4P IE3

Rated current : 11.0 A
LRC : 5.6
Rated torque : 3.74 kgfm
Locked rotor torque : 180 %
Breakdown torque : 220 %
Rated speed : 1455 rpm

Moment of inertia (J) : 0.0566 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 4 / 6Revision		
Checked by				
Date	28/07/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM
NEMA Premium Efficiency Three-
Phase

Product code : 14495396



Performance : 400 V 50 Hz 4P IE3

Rated current : 10.6 A
LRC : 6.2
Rated torque : 3.73 kgfm
Locked rotor torque : 190 %
Breakdown torque : 240 %
Rated speed : 1460 rpm

Moment of inertia (J) : 0.0566 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 6Revision		
Checked by				
Date	28/07/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM
NEMA Premium Efficiency Three-
Phase

Product code : 14495396



Performance : 415 V 50 Hz 4P IE3

Rated current : 10.4 A
LRC : 6.7
Rated torque : 3.72 kgfm
Locked rotor torque : 210 %
Breakdown torque : 260 %
Rated speed : 1465 rpm

Moment of inertia (J) : 0.0566 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 6 / 6Revision	
Checked by					
Date	28/07/2026				

