DATA SHEET

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : Rolled Steel 00022 Single-Phase Product code : 15793862

Frame	: 213/5T	Locked rotor time	: 16s (cold) 9s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 230 V	Ambient temperature	: -20°C to +40°C
Poles	: 4	Altitude	: 1000 m.a.s.l.
Rated current	: 28.8 A	Protection degree	: IP55
	: 9.0x(Code J)	Cooling method	: IC411 - TEFC
Rated speed	: 1755 rpm	Mounting	: F-1
Rated torque	: 3.10 kgfm	Rotation[1]	: Both (CW and CCW)
Insulation class	: F	Noise level[2]	: 64.0 dB(A)
Service factor	: 1.15	Starting method	: Direct On Line
Moment of inertia (J)	: 0.0605 kgm²	Approx. weight[3]	: 74.0 kg

Output	25%	50%	75%	100%
Efficiency (%)	0.000	78.5	84.0	85.5
Power Factor	0.00	0.95	0.96	0.97

Foundation loads

Max. traction	: 135 kgf
Max. compression	: 209 kgf

		Drive end	Non drive end
Bearing type	:	6208 2RS	6206 2RS
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	0 h	0 h
Lubricant amount	:	0 g	0 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	11/05/2026		1 / 2	


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage

Customer :


Product line : Rolled Steel 00022 Single-Phase Product code : 15793862





Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	11/05/2026		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice









ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

Mounting F-1/B3R(D)

EXECUTED	HYBRISUSER	SINGLE PH. MOTOR ROLLED STEEL FARM DUTY	PREVIEW
CHECKED		FRAME 213/5T IP55 TEFC	WDD 00
RELEASED			
REL. DATE		WMO Jaragua do Sul Product Engineering	SHEET 1 / 1

7.5 HP 04 Poles 60 Hz

A

Dimensions in inches

XME A3

WEG's property. Forbidden reproduction without previous authorization.